



TORMAX Series TX9420TL HD Trackless Telescoping Automatic Sliding Door Outside Slide

iMotion® 2401 Heavy Duty Direct Drive System

Unit Features

- Series TX9420TL HD Trackless Outside Slide - Concealed or Surface Mount Models for New Construction, Retrofit or Remodel Applications. Other Models Include the Flush Mount Utility Header and Trolleys When Doors are Supplied by Others.
- Outside Slide - Only Sliding Doors Breakaway for Emergency Egress
- Access Control Package Option is Available - Electric Locking With Flush Mount Concealed Vertical Rod Exit Panic Hardware
- AC Synchronous .40 HP Motor With Built-In Motor Protection Circuit - No Gears to Wear, No Leaking Oil or Grease. No Motor Brushes, Commutator or Couplings to Replace. "Wear Free Drive Principle"
- Smooth and Silent Operation (sound level less than 70 DB) - "Silent Drive" Unlimited Application Opportunities
- Robust High Speed/High Torque .40 HP AC Motor - Capable of Sliding Single Door Leafs Weighting up to 265 Pounds (120KG), Biparting Door Leafs Weighting up to 220 Pounds (100KG) Each
- Optional IP.65 Heavy Duty Direct Drive - Ideal for Highly Corrosive Environments, Stainless, Dust Proof and Protected From Jetting Water. Drive System Components Manufactured From 316 Marine Stainless Steel
- Panels are Synchronized to Open Together via Gear Reduction Unit - No Maintenance Prone Pulleys and Cables Required
- Heavy Duty Interlocked Panel Design - Provides for Consistent Performance Through Heavy Use, Eliminates Panel Twist and Unsightly Joint Lines
- Door Panel Design - Corner Block Construction for Maximum Strength and Durability With Minimum 1/8" (3) Aluminum Wall Thickness, Available in Narrow and Medium Stile Design With Optional Rail Profiles
- Security Glazing Stops - Prevents Removal of Glass From Exterior, Available for 1/4" (6), 5/8" (16) and 1" (25) Thick Glass
- Spring Return Closers as Standard on Sliding Doors - Controls the Direction of Swing in the Event of a Breakaway Condition
- Door Support and Suspension - Two Independent Trolley Heads Consisting of (4) 2 1/2" (64) Diameter Nylon Rollers With Precision Steel Lifetime Lubricated Closed Ball Bearing Centers and (2) Anti-Riser Rollers to Prevent Derailing

- Trolley Heads Provide for Vertical and Lateral Door Adjustments - Simplifies the Installation and Allows for Optimal Positioning of the Door Panels
- Field Replaceable Hard Coat Anodized Aluminum Door Roller Track, Isolated Between a Rubber Isolation Pad - Provides for a Smooth and Quiet Ride
- Heavy Duty 7/8" (22) Fiberglass Reinforced Nylon Drive Belt - Sound Absorbing Material With Long Life Span, Maintenance Free
- Self-Supporting Header With Hinged Cover - Minimal Deflection at 14'-0" (4267) Unit Width
- Two Microprocessor Self-Monitoring Doorway Holding Beams - Monitored for Proper Operation Every 20 Seconds and After Each Opening Cycle
- Universal iMotion® Microprocessor Controller – One Common Controller for All iMotion® Drives
- Plug and Play iMotion® Microprocessor Control System - Self-Calibrates Opening and Closing Positions, Door Speeds and Time Delays for Optimal Performance Based on the Door Weight and the Operating Environment
- No Mechanical Switches and/or Cams Required for Door Position - Eliminates Costly Service and Down Time
- Self-Adjusting iMotion® Microprocessor Control System - Auto-Compensates During Operation to Maintain Established Operating Parameters
- Programmable iMotion® Microprocessor Control System - Provides Flexibility During System Configuration, No Special Tools Required
- Integrated Access Code to Inhibit Unauthorized Door Adjustments - Programmable
- On-Board Power Supply Output With Overload Protection (24VDC .75A Max) as Standard for Activation and Safety Sensors - No Auxiliary Transformer Required
- Two On-Board Outputs (24VDC) for Door Position Status, Alarm, Etc. - Programmable
- Four On-Board Inputs for Safety - Programmable
- Four On-Board Inputs for Activation, Key Switch and Mode of Operation - Programmable, Key Switch Remains Enabled in Off Mode for Access Control Integration
- Factory Reset - Programmable
- Optional I/O Module - Provides Four Additional Inputs and Four Additional Outputs
- Illuminated Seven-Segmented Function Control Panel - Provides for Six Operating Modes, System Configuration and Auto-Diagnostics
- Function Control Panel - Off/Automatic/Auto Reduced Open/Exit /Hold Open/Manual
- Door Motion Settings (door speeds and time delays) - Programmable via Function Control Panel
- Reduced Opening Width - Programmable via Function Control Panel
- Function Control Panel Security - Provided via Optional Key Switch
- Manual Override (free wheeling) Friction Free Manual Operation - Selectable via Function Control Panel
- Auto Diagnostics via Function Control Panel - Provides for Quick and Simple Troubleshooting
- Electronic Reversing for Door Obstruction in the Opening Direction - Door Will Stop and Reverse Close
- Electronic Reversing for Door Obstruction in the Closing Direction - Door Will Stop and Reverse Open
- Reversing Sensitivity Adjustment - Programmable

- Full Range of Door Operating Sensors and Manual Controls Available - ANSI Compliant
- Optional Accessories Available - Battery Back-Up, Electric Lock, Security Monitoring of Sliding Door Position, People Counting Devices and Other Door Auxiliary Hardware
- Complete Range of Heavy Duty Aluminum Threshold Profiles Available - Recessed, Surface Double Bevel and Combination Surface Bevel/Square
- Standard Architectural Class 1 Anodized Finishes Clear and Dark Bronze - Other Anodized Finishes, Painting and Metal Cladding Available Upon Request
- Global Power Supply - Selectable 115-230VAC 50-60 HZ, Single Phase
- Power Consumption - Max 310 Watt
- ANSI Compliant - Meets or Exceeds ANSI A156.10 Standards
- ANSI/ULC 325 Listed - United States and Canada