



## TORMAX Series TX9600TLSR Intensive Care Unit Trackless Smoke Rated Manual Sliding Door (ICU)

### Unit Features

- TX9600TLSR ICU Sliding Door - UL1784 Smoke and Draft Control Listing
- Trackless Design - No Floor Track or Threshold Required
  - Eliminates Buildup of Potential Contaminants in Floor Tracks
  - Provides for Smooth Transition of Sensitive Medical Equipment Between Rooms
- Two Panel Design - Single Slide Maximum Height 96" (2348) x Maximum Width 108" (2743)
- Four Panel design - Bi-part Slide Maximum Height 96" (2348) x Maximum Width 144" (3658)
- Positive Latching as Standard - Sliding Panel is Latched in the Full Closed Position. Lever Handles Facilitate the Unlatching of the Sliding Door. Breakaway Release of the Slide and Swing Out Panel is Achieved in the Full Open Position
- Silicone Smoke Rated Seals as Standard - Eliminate Contaminant Buildup and Easy to Clean
- Optional Bottom Rail Seal - Required Where Positive Pressure is Used to Control the Movement of Smoke
- Optional Self Closing Mechanism - Airborne Infection Isolation Rooms (Requires Positive Latching)
- Units are Electrostatic Grounded - Prevents Accidental Static Discharge
- Attractive Slim Line Construction - Aesthetically Pleasing
- Hinged Access Cover - Provides for Ease of Access for Preventative Maintenance
- Sliding Doors (SX) and Adjacent Swing Out (SO) Panels Breakaway Without the Facilitation of Flush Bolts to 90 Degrees - Quick and Easy Access to Patients is Assured
- Anti-Sag/Riser Roller Support - Prevents Doors From Derailing and Provides Sag-Free Construction and Support for Panel Breakout
- Unique Concealed Bottom Guide System - Eliminates Floor Mounted Transfer Pivots
- Sliding Panel Restrictor Bracket - Prevents Accidental Breakout and Eliminates the Need for Flush Bolts.
- Large Expansive Glazed Panels for Visibility to Patients and Waiting Areas - Panels can be Factory Prepared to Accept Switchable LC Privacy Glass to Maintain Patient Privacy and Dignity at all Times.
- Door Panel Design - Corner Block Construction for Maximum Strength and Durability With Minimum 1/8" (3) Aluminum Wall Thickness, Available in Narrow and Medium Stile Design With Optional Rail Profiles, Sized to Eliminate Pinch Points
- Security Glazing Stops - Prevents Removal of Glass From Exterior, Available for 1/4" (6), 5/8" (16) and 1" (25) Thick Glass
- Heavy Duty Interlocked Panel Design - Provides for Consistent Performance Through Heavy Use, Eliminates Panel Twist and Unsightly Joint Lines
- Insulated Glass Panels - Limit Sound Migration Between Medical, Patient and Waiting Areas

- Gentle Touch Trolley Head Assemblies - Doors Slide With Quiet Efficiency and Minimal Effort
- Sliding Doors are Supported by (2) Tandem Trolley Assemblies, Each Consisting of (2) Nylon Wheels With Precision Steel Lifetime Lubricated Closed Ball Bearing Centers - Provides for Prolonged Life and Silent Operation
- Vertical Door Adjustment - Provides for Ease of Installation
- Standard Architectural Class 1 Anodized Finishes Clear and Dark Bronze - Other Anodized Finishes, Painting and Metal Cladding Available Upon Request