



Tormax Series TX 9000 Slide Door Package

Date: _____

Company Name _____	Customer OP # _____
Contact Person _____	TX Series # _____
Phone # _____	Unit Configuration, i.e.(P-SX) _____
Fax # _____	Unit Quantity _____
	Finish/Color _____

Package Information

Package width- Including side jambs
Package height FFF to top of header
Package height FFF to top of transom
Function control panel installed

Specify:

Dimension _____
Dimension _____
Dimension _____
Cover _____ Header Face (opposite cover side) _____
Remote _____ Cable Length _____
RH → _____ LH ← _____ Bi-part ↔ _____

Slide direction (viewed from exterior)

Note: consult detail application drawings for TX9300 and TX9420 utility packages

Standard Options

Maximum opening (equal panels)
Horizontal muntin bar 1 3/4"
Bottom rail 4"
Glass thickness 1/4"
TX9500 AG no glass
Narrow stile panels
Vertical in transom (BP One vertical)
Delta III sensors (Optex iOne)
Half thresholds (recessed)
iMotion® 2301 Std duty drive system

Specify options per panel:

DOW _____ Specify MO _____
No Muntins _____ 1 3/4" Qty. _____ 4 1/2" Qty. _____ 9" Qty. (seemed) _____
8" _____ 10" _____ **14" _____ **16" _____ () seemed options
5/8" or 1" SO _____ SX _____ O _____ Transom (1/4" or 1") _____
1/2" clear _____ 1/2" tinted _____ Specify tint _____
Medium stile panels _____
Qty. _____ Center _____ Over the sidelights _____ Equal glass _____
Sigma (G3) _____
Double bevel _____ Bevel (ext)/Square (Int) _____ Square (ext)/Bevel (Int) _____

Optional Materials

Continuous threshold

Adjacent SO or O panel (provide sketch)
Horizontal in transom (provide sketch)

Optional Accessories

Access control (electric lock & flush mount panic hardware)
Electric lock only
Electric lock- lock position
I/O module (2301, 2401, TEP.IP65 & TXP.IP65)
Battery back-up
Function control panel key switch (inhibit FCP)
SX Door roller support
SO Panel bottom ball detent
DPS- monitors SX & SO panel position
Doorway holding beam (not required by design)
Mechanical lock w/ cyl (not required by design)
Recessed pull handle (not required by design)
Cylinder guard
Lock indicator
Interchangeable cylinder housings w/o Best core
Flush bolt installed (not required by design)
Dust proof strike installed
Armored strike installed
DPDT Relay

Specify:

Double bevel _____
Bevel (ext)/ Square (int) _____
Square (ext/ Bevel (Int) _____
Recessed _____
Qty. _____ SO _____ O _____
Yes _____

Specify:

Fail secure _____ Fail safe _____
Surface mount panic hdwr _____
Fail secure _____ Fail safe _____
Off and exit only mode _____ Off mode _____ All modes _____

Qty. _____
Yes _____
Surface mount _____ Flush mount _____
Yes _____

Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____

Other: Specify _____

Other special material, accessories, and/or programming (theory of operation), requirements / applications: Specify _____

All muntin dimensions are from the bottom of the package to the centerline of the muntin bar
TX9200 and TX9420 std. muntin bar height to centerline of bar = 42 3/4"
TX9300 and TX9430 std. muntin bar heights to centerline of bar = 42 1/2"
TX9600TL, TX9600, TX 9630TL & TX9620 std. muntin bar height to centerline of bar = 40"

NOTE: TO EXPEDITE YOUR ORDER, COMPLETE THIS FORM FOR EACH TYPE OF DOOR PACKAGE.