



Tormax 1201 Swing Door Operator- LE & HE  
Side Load Header & Slim Line Cover Order Form

Tormax 1201 Swing Door Operator LE & HE

Date: \_\_\_\_\_

Company Name \_\_\_\_\_  
Contact Person \_\_\_\_\_  
Phone # \_\_\_\_\_  
Fax # \_\_\_\_\_

Customer PO# \_\_\_\_\_  
Job Name \_\_\_\_\_  
Type - Operator Housing Assembly  
1201SL \_\_\_\_\_ Qty. \_\_\_\_\_  
1201.Fire SL \_\_\_\_\_ Qty. \_\_\_\_\_  
1201SLC \_\_\_\_\_ Qty. \_\_\_\_\_

**Side Load Header**

Tormax 1201 Stock Header Length = 31 1/2" Non-Handed Header \_\_\_\_\_ or Full Length Header \_\_\_\_\_

**Slim Line Cover & Backplate** **Optional Charge**

Tormax 1201SLC Length 51 1/2" \_\_\_\_\_ or 101 1/2" \_\_\_\_\_ Cut cover & backplate to length and prep cover w/spindle cutout \_\_\_\_\_

**Door Arms**

**Push Application**

Outswing (Reveal 0-4 3/8") Qty. \_\_\_\_\_ Color: Clear \_\_\_\_\_ Black \_\_\_\_\_  
Outswing (Reveal 4 1/8"-9 7/8") Qty. \_\_\_\_\_ Color: Clear \_\_\_\_\_ Black \_\_\_\_\_

**Pull Application**

Inswing door arm w/ track (0" Reveal) Qty. \_\_\_\_\_ Color: Clear \_\_\_\_\_ Black \_\_\_\_\_  
RH inswing double egress door arm w/ track (Reveal 0-6") Qty. \_\_\_\_\_ Color: Clear \_\_\_\_\_ Black \_\_\_\_\_  
LH inswing double egress door arm w/ track (Reveal 0-6") Qty. \_\_\_\_\_ Color: Clear \_\_\_\_\_ Black \_\_\_\_\_

**Information Required for Side Load Header Full Length Header Fabrication**

Full length header calculation = Nominal door panel width + 1 3/4" overlap on each side of Frame

Standard overlap each side ( 1 3/4" ) \_\_\_\_\_

Other (specify overlap of each side of frame ) \_\_\_\_\_ Total Overlap \_\_\_\_\_

**Application**

Single \_\_\_\_\_  
Simultaneous Pair \_\_\_\_\_  
Double Egress \_\_\_\_\_

**Hand of Swing**

RH \_\_\_\_\_ LH \_\_\_\_\_  
RH/LH \_\_\_\_\_  
RH/RH \_\_\_\_\_ LH/LH \_\_\_\_\_

**Pivot Type**

Butt \_\_\_\_\_  
Offset 5/8" \_\_\_\_\_ Offset 3/4" \_\_\_\_\_ Other: \_\_\_\_\_  
Center Pivot \_\_\_\_\_ w/ 1" FG \_\_\_\_\_ W/O FG \_\_\_\_\_  
Other: Specify \_\_\_\_\_

**Door Panel Width (Nominal)**

24" \_\_\_\_\_  
30" \_\_\_\_\_  
36" \_\_\_\_\_  
42" \_\_\_\_\_  
44" \_\_\_\_\_  
48" \_\_\_\_\_  
Special: Specify \_\_\_\_\_

**Swing Type**

Outswing (push) \_\_\_\_\_ Specify Reveal \_\_\_\_\_  
Inswing (pull) \_\_\_\_\_ Specify Reveal \_\_\_\_\_ **(emergency breakout not available)**

**Optional Accessories**

Exterior Door Module (EDM) Qty. \_\_\_\_\_  
Power Door Module (PDM) Qty. \_\_\_\_\_  
Multiple Door Module (MDM) Qty. \_\_\_\_\_  
Programming Interface Module (PIM) Qty. \_\_\_\_\_  
iMotion Programmer w/ 6' Cable Qty. \_\_\_\_\_  
(Interfaces w/ PIM & EDM) Battery  
Backup w/39" harness Battery Qty. \_\_\_\_\_  
Backup Extension harness Qty. \_\_\_\_\_  
On/Off/Hold Open Key Switch Qty. \_\_\_\_\_  
AC/DC 24V 2.5 Amp Power Supply Qty. \_\_\_\_\_  
(Motorized Panic Hardware)  
Concealed Closer Qty. \_\_\_\_\_  
ARM Stop Qty. \_\_\_\_\_

**Finish - Anodize/Other**

\_\_\_\_\_ Clear (215 or AA-M12-C21-A41)  
\_\_\_\_\_ Dark Bronze (313 or AA-M12-C22-A44)  
\_\_\_\_\_ Black (315 or AA-M12-C22-A44)  
\_\_\_\_\_ Mill Finish  
\_\_\_\_\_ Other Anodizing  
\_\_\_\_\_ Other Paint  
\_\_\_\_\_ Other Metal Cladding

Other Comments: \_\_\_\_\_