

TX9600 MANUAL INTENSIVE CARE UNIT(I.C.U.)

THRESHOLD DETAIL - RECESSED THRESHOLD TRACK DATE:_____ JOB NAME: DOOR NO:_____SHEET___OF_ DOOR LOCATION: __ RECESSED THRESHOLD EXTRUSION - 4 1/2" FRAME NOTE: 1. RECESSED THRESHOLD TRACK REQUIRED AT "SO" PANEL(S) ONLY. RECESS SHALL INCLUDE EACH JAMB TUBE AS WELL. RECESS IS 1/2"(13) IN DEPTH x 4 5/8"(117) IN WIDTH. LENGTH IS DETERMINED BY "SO" PANEL WIDTH. 2. CONTINUOUS RECESSED THRESHOLD TRACK IS OPTIONAL. FILTER STRIP IS USED AT SLIDE DOOR OPENING. **EXTERIOR INTERIOR** .203"(5) FILTER STRIP (114)PLAN SINGLE SLIDE FOR SINGLE SLIDE RECESSED THRESHOLD TRACK "SO" PANEL WIDTH = 1/2 PACKAGE WIDTH -9/16"(14) 2"(51) "SO" WIDTH +2"(51) ROUGH OPENING **EXTERIOR PLAN** BI-PART "SO" PANEL WIDTH = 1/4 PACKAGE WIDTH +11/32"(9) FOR BI-PART RECESSED THRESHOLD TRACK "S0" WIDTH +2"(51)"SO" WIDTH +2"(51) ROUGH OPENING **EXTERIOR**