
TO	R	M	Δ	X		
		MA.				

TTX 1102 LOW ENERGY SWING DOOR OPERATOR

SIMULTANEOUS PAIR, W/CONTINUOUS HEADER, VISIBLE INSWING

AUTOMATIC	CENTER PIVOT NON-	-PANIC APPLICAT	ION			
JOB NAME:		DATE:				
DOOR LOCATION	•	DOOR NO:	SHEET	OF		
TTX 1102 HEADER ELEV	CONTROLS—— ELECTRICAL—— ATION IOR	ACCESS COVER 4 9/16" [116] 7/8" [22] REVEAL FROM TH THE DO REAR OF	ELECTRICAL CONTROLS TTX 1102 OPERATOR OPERATOR DISTANCE HE FACE OF OR TO THE OPERATOR OPERATOR VERTICAL SECTI	1 1/8" [28] ON		
INTERI PLA		- 2 2/+ [a2] -		HAFT /4"[95] 3/4"(44)		
NOTES: 1. DETAILS NOT TO SCALE. 2. ELECTRICAL REQUIREMENTS: 1. 120VAC, 5AMPS MIN. TO OPERATOR BY ELECTICAL CONTRACTOR. 3. DOORS, FRAMES AND HARDWARE BY OTHERS. 4. 32" CLEAR DOOR OPENING REQUIRED TO MEET A.D.A. REQUIREMENTS.						
5. DOORS MUST BE NON-LATCHED FOR PROPER OPERATION.						