



TORMAX TX9200/TX9300/TX9400/TX9500 Powered Slide Door Package

Date: _____

Company Name _____	Customer PO # _____
Contact Person _____	TX Series # _____
Phone Number _____	Unit Configuration, i.e. (P-SX) _____
Cell/Fax # _____	Unit Quantity _____
Email _____	Finish / Color _____

Package Information

Package Width - Including side jambs
Package Height - FFF to Top of Header
Package Height - FFF to Top of Transom

Specify:

Dimension _____
Dimension _____
Dimension _____

FCP, Shipped Loose w/ SM Box & 14' Cable (Standard) _____
Optional Cable Lengths: 25' ___ 50' ___ 75' ___ 98' ___

Optional Cover-Mounted (9300/9430/9500FBO) _____
Opt Header-Face Mounted (9200/9420/9500FSL) _____

On/Off/Hold Open, 3-Position Rocker Switch (Optional) _____
On/Off, 2-Position Rocker Switch (Optional) _____

Specify: On/Off/Hold Open _____ On/Off/Exit _____

As standard, Rocker Switches will be factory-installed to the underside of header, and FCP will be factory-installed inside the header. If other, please specify: _____

Slide Direction (viewed from exterior) RH → _____ LH ← _____ Bi-Part ↔ _____

Standard Options

Maximum Opening (Equal Panels)
Horizontal Muntin Bar (1-3/4")
Bottom Rail (4")
Panel Stops for 1/4" Thick Glass
Transom Vinyl for 1/4" Thick Glass
Top Horizontal Transom "Can"
TX9500 AG (No Glass)
Narrow Stile Panels
Vertical in Transom (BP, One Vertical Std)
(2) TORMAX 7501 (Monitored Sensors)
Half Thresholds, Recessed (TX9300 Only)
(2) Doorway Holding Beams (Monitored)
iMotion® 2301 Standard Duty Drive System

Specify Options Per Panel:

DOW _____ Specify MO Height & Width _____
No Muntins _____ 1-3/4" Qty. _____ 4-1/2" Qty. _____ 10" Qty. _____
10" _____ 14"*** _____ 20"*** _____ (***) Seamed Options
Optional Stops (3/8", 1/2", 5/8", 3/4", 7/8", 1") SO _____ SX _____ O _____
Optional Vinyl (5/8", or 1") _____
Substitute Top Horizontal Transom "Tube" _____
1/2" Clear _____ 1/2" Tinted _____ Specify Tint _____
Medium Stile Panels _____
Qty. _____ Center _____ Over the Sidelites _____ Equal Glass _____
(2) BEA IXIO (Monitored) _____ (2) Optex iOne XT (Monitored) _____
Bevel (Ext) / Square (Int) _____ Surface Sweeps _____
iMotion® 2401 Heavy Duty Drive System _____ iMotion® 2301.IP65 System _____
iMotion® 2401.IP65 HD System _____ Manual Operation (Delete Drive) _____

Optional Materials

Continuous Threshold
Adjacent SO or O Panel (Provide Sketch)
Horizontal in Transom (Provide Sketch)

Specify:

Double Beveled _____ Recessed (Square) _____
Bev (Ext) / Square (Int) _____ Square (Ext) / Bev (Int) _____
Qty. _____ SO _____ O _____
Yes _____

Optional Accessories

Access Control (Electric Lock & Flush-Mounted Panic Hardware)
Electric Lock Only
Electric Lock - Lock Position
I/O Module (2301, 2401)
Battery Back-up
Function Control Panel Key-Switch (Inhibit FCP)
SO Panel Bottom-Ball Detent
DPS - Monitors SX & SO Panel Position & Breakout
Brake Disconnect Relay Assembly
Air-Curtain Relay
Mechanical Lock w/ cyl (not required by design)
Chrome Recessed Pull Handle (not req. by dsgn)
Cylinder Guard
Lock Indicator
Interchangeable Cylinder Housings w/o Best Core
Flush Bolt Installed (not required by design)
Dust Proof Strike Installed
Armored Strike Installed
24vDC DPDT Relay & Bracket
SS FM Four Position Key-Switch Maintained w/ Cylinder (Off/Exit/Auto/Hold Open)
SS FM Jamb Key-Switch SPST Momentary (N.O.) w/ Mortise Cylinder (On/Off)
Three Position Key Switch

Specify:

Fail Secure _____ Fail Safe _____
Match 4-1/2" Muntin on opposing Vestibule Slider _____
Fail Secure _____ Fail Safe _____
Off & Exit Only Mode _____ Off Mode _____ All Modes _____
Yes _____
Yes _____
Surface-Mounted _____ Flush-Mounted _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____ Other: Specify _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____

Other Special Materials, Accessories, and/or Programming (Theory of Operation), Requirements / Applications: _____

All muntin dimensions are from the bottom of the package to the centerline of the muntin bar.

TX9200 and TX9420 standard muntin bar height to centerline of bar = 42-3/4"

TX9300 and TX9430 standard muntin bar height to centerline of bar = 42-1/2"

NOTE: TO EXPIDITE YOUR ORDER, COMPLETE THIS FORM FOR EACH TYPE OF DOOR PACKAGE.