



Tormax Series TX9650 ICU Manual Swing Unit

Date: _____

Company Name _____

Customer PO # _____

Phone # _____

Contact Person _____

Unit Quantity _____

Fax # _____

Finish: Clear Anodized (215 or AA-M12-C21-A41) _____ Dark Brz Anodized (313 or AA-M12-C22-A44) _____

Other Specify: _____

Series Type: TX9650 _____ TX9650SR _____

Swing Type: Single (One Panel) _____ Pair (Unequal Pair) _____ Pair (Equal Pair) _____

HL- * 5\$'Sk]b['Unit'DfcXi Wi7 cbZ[i fU]cb

Swing type: Single SO RH _____ Single SO LH _____
Pair (Unequal) SO-SO LH _____ Pair (Unequal) SO RH-SO _____
Pair (Equal) SO LH - SO RH _____

Package Information:

Package width - Including side jambs
Package height - FFF to top of header
Package height - FFF to top of transom
Nominal Door Panel Width

Specify:

Dimension _____ TX9650SR Max Single (51 1/2") Pair (99 1/2")
Dimension _____ TX9650SR Max 96"
Dimension _____ TX9650SR Not Available
SO Active _____ SO Inactive _____

Standard Options:

Horizontal Muntin bar 1 3/4"
Bottom Rail 4"
Glass Thickness 1/4"
Narrow Stile Panels
Vertical in transom (non-standard)

Specify options per panel:

No Muntins _____ 1 3/4" Qty _____ 4 1/2" Qty _____ 10" Qty _____
10" _____ **14" _____ **16" _____ (**) seamed options
1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 7/8" or 1" SO _____ Transom (1/4", 5/8", or 1") _____
Medium Stile panels _____
Center _____

Optional Accessories:

Mechanical lock w cyl
Cylinder guard
Lock Indicator
Armored Strike installed
Automatic Door Bottom Seals for Pressurized Rooms
Interchangeable cylinder housings w/ or w/out core
Other special material accessories, and/or, requirements/applications:

Specify:

Yes _____
Yes _____
Yes _____
Yes _____
Yes _____
Yes _____ Other Specify: _____
Specify: _____

All muntin dimensions are from the bottom of the package to the centerline of the muntin bar
TX9650 & TX9650SR standard muntin bar height to centerline of bar = 40"
Note: TO EXPEDITE YOUR ORDER, Complete this form for each type of door package.